SR GT 125 - TECHNICAL SPECIFICATIONS

Engine	Single-cylinder 4-stroke i-get with Start & Stop system
Engine capacity	125 cc
Bore x stroke	52 mm x 58,7 mm
Max. power	11 kW @ 8.900 rpm
Max. Torque	12 Nm @ 6.750 rpm
Consumption	2,5 l/100 km
CO2 Emissions	60 g/km
Valve timing system	Single overhead camshaft, 4 valves
Cooling	Liquid
Fuel system	Electronic injection
Lubrication	Wet sump
Starter	Electric
Transmission	Continuously variable transmission (CVT)
Clutch	Automatic centrifugal dry clutch
Chassis	Double cradle, in high-resistance steel tubing
Front suspension	Hydraulic telescopic fork ø 33 mm (120 mm travel)
Rear suspension	Double hydraulic shock absorber with adjustable preload (102 mm travel)
Front brake	Hydraulic with wave disc Ø 260 mm ABS
Rear brake	Hydraulic with wave disc Ø 220 mm
Front tyre	110/80 - 14"
Rear tyre	130/70 - 13"
Length	1.920 mm
Width	765 mm
Seat height	799 mm
Wheelbase	1.350 mm
Fuel tank capacity	9 l
Emissions compliance	EURO 5+